# **PANZERI**

# Silver Ring

220-240V AC dimmable (DALI/Push DIM)

P08201.180.0402

## white



#### Data sheet

| CODE                       | P08201.180.0402          |
|----------------------------|--------------------------|
| SYSTEM POWER CONSUMPTION   | 110W                     |
| EFFICACY                   | 71.36lm/W                |
| LIGHT SOURCE               | LED                      |
| COLOUR TEMPERATURE         | 3000K Ra>90              |
| LIGHT DISTRIBUTION         | diffused                 |
| POWER SUPPLY               | 220-240V AC              |
| FREQUENCY                  | 50/60Hz                  |
| ELECTRICAL CONFIGURATION   | dimmable (DALI/Push DIM) |
| DRIVER                     | integrated included      |
| NOMINAL LUMINOUS FLUX      | 15716lm                  |
| LUMEN OUTPUT               | 7850lm                   |
| EFFICIENCY                 | 49.9%                    |
| WEIGHT                     | 18,86 Kg                 |
| PROTECTION DEGREE          | IP40                     |
| COLOUR TOLLERANCES         | SDCM 3                   |
| GLOW WIRE TEST PERFORMANCE | 850°                     |
| PACKING DIMENSIONS         | 200,0 x 18,0 x 200,0 cm  |
|                            |                          |



Ceiling or wall lighting fixture for interiors, with direct light emission.

Pickled sheet metal ceiling/wall bracket in polyacrylic paint.

Pickled sheet metal structure in polyacrylic paint.

Aluminium dissipation plates.

Pickled sheet metal covers in white, black or bronze polyacrylic paint, or with gold leaf

 $\label{thm:modelled} \mbox{Modelled polycarbonate diffuser with opaline finish.}$ 








# Technical drawing






### **Application**



#### Polar diagram



cd/klm C0 - C180 - - - C90 - C270