PANZERI

Superbold

220-240V AC dimmable (phase cut)

P08801.060.0404

white



Data sheet

CODE	P08801.060.0404
SYSTEM POWER CONSUMPTION	32W
EFFICACY	67.66lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (phase cut)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	4856lm
LUMEN OUTPUT	2165lm
EFFICIENCY	44.6%
WEIGHT	4,17 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm

Ceiling or wall lighting fixture for interiors, with direct light emission.

 $Turned\ steel\ structure\ in\ white,\ mat\ black,\ champagne,\ bronze,\ textured\ myrtle\ blue\ and$ textured natural terracotta polyacrylic paint.

Aluminium wiring support plate with polyacrylate paint finish.

Curved diffuser screen made of matt PMMA technopolymer.








Technical drawing





Application

