PANZERI

Superbold

220-240V AC dimmable (phase cut)

P08829.045.0504





Data sheet

CODE	P08829.045.0504
SYSTEM POWER CONSUMPTION	21W
EFFICACY	67.33lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (phase cut)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3172lm
LUMEN OUTPUT	1414lm
EFFICIENCY	44.6%
WEIGHT	2,22 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm




Ceiling or wall lighting fixture for interiors, with direct light emission. $Turned\ steel\ structure\ in\ textured\ soft\ white,\ mat\ black,\ champagne,\ bronze,\ textured$ myrtle blue and textured natural terracotta polyacrylic paint. Aluminium wiring support plate with polyacrylate paint finish. Curved diffuser screen made of matt PMMA technopolymer. DALI/Push DIM driver available on request.







Technical drawing



Application

