## PANZERI

### Superbold

220-240V AC dimmable (phase cut) P08829.060.0504

#### Data sheet

CODE	P08829.060.0504
SYSTEM POWER CONSUMPTION	32W
EFFICACY	66.31lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (phase cut)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	4758lm
LUMEN OUTPUT	2122lm
EFFICIENCY	44.6%
WEIGHT	4,17 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



textured natural terracotta






Ceiling or wall lighting fixture for interiors, with direct light emission. Turned steel structure in white, mat black, champagne, bronze, textured myrtle blue and textured natural terracotta polyacrylic paint. Aluminium wiring support plate with polyacrylate paint finish. Curved diffuser screen made of matt PMMA technopolymer.

# CE ERE 🗵

### Technical drawing



### Application

