

# PANZERI

## Ginevra

220-240V AC dimmable (DALI/Push DIM)

P09280.030.0502

 black/gold

DIRECT  
LIGHT


### Data sheet

CODE	P09280.030.0502
SYSTEM POWER CONSUMPTION	15W
EFFICACY	93.13lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1804lm
LUMEN OUTPUT	1397lm
EFFICIENCY	77.4%
GLARE RATING	UGR < 19
WEIGHT	2,00 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	46,0 x 46,0 x 16,0 cm



Ceiling or wall lighting fixture for interiors, with direct light emission.  
Turned aluminium structure in mat black and gold or white and gold polyacrylic paint.  
Pickled sheet metal wiring support plate in polyacrylic paint.  
Moulded PMMA micro-prismatic diffuser.

### Technical drawing



### Application

