# **PANZERI**

## Ginevra

220-240V AC tunable white

P09280.050.9017





#### Data sheet

| CODE                     | P09280.050.9017          |
|--------------------------|--------------------------|
| SYSTEM POWER CONSUMPTION | 30W                      |
| EFFICACY                 | 59.8lm/W                 |
| LIGHT SOURCE             | LED                      |
| LIGHT SOURCE LIFETIME    | L80 (B20) 80.000h        |
| COLOUR TEMPERATURE       | 2700-6500K Ra>90         |
| LIGHT DISTRIBUTION       | diffused                 |
| POWER SUPPLY             | 220-240V AC              |
| FREQUENCY                | 50/60Hz                  |
| ELECTRICAL CONFIGURATION | tunable white            |
| DRIVER                   | integrated included      |
| NOMINAL LUMINOUS FLUX    | 2963lm min. / 3380lm max |
| LUMEN OUTPUT             | 1794lm min. / 2046lm max |
| EFFICIENCY               | 60.5%                    |
| GLARE RATING             | UGR < 19                 |
| WEIGHT                   | 5,22 Kg                  |
| PROTECTION DEGREE        | IP20                     |
| COLOUR TOLLERANCES       | SDCM 3                   |
| PACKING DIMENSIONS       | 58,0 x 58,0 x 14,0 cm    |
|                          |                          |




Ceiling or wall lighting fixture for interiors, with direct light emission.  $Turned\ aluminium\ structure\ in\ mat\ black\ and\ gold\ or\ white\ and\ gold\ polyacrylic\ paint.$ Pickled sheet metal wiring support plate in polyacrylic paint.  $\ \, \text{Moulded polycarbonate micro-prismatic diffuser}.$ 








### Technical drawing



### **Application**



#### Polar diagram



cd/klm C0 - C180 - - - C90 - C270