PANZERI

Ginevra

220-240V AC tunable white
P09280.050.9017

matte black - brass

DIRECT LIGHT

Data sheet

CODE	P09280.050.9017
SYSTEM POWER CONSUMPTION	30W
EFFICACY	59.8lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	2700-6500K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	tunable white
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2963lm min. / 3380lm max
LUMEN OUTPUT	1794lm min. / 2046lm max
EFFICIENCY	60.5%
GLARE RATING	UGR < 19
WEIGHT	5,22 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	58,0 x 58,0 x 14,0 cm



Ceiling or wall lighting fixture for interiors, with direct light emission.
Turned aluminium structure in mat black and gold or white and gold polyacrylic paint.
Pickled sheet metal wiring support plate in polyacrylic paint.
Moulded polycarbonate micro-prismatic diffuser.

Technical drawing



Application



Polar diagram

