PANZERI

Ginevra

220-240V AC tunable white

P09280.050.9017





Data sheet

CODE	P09280.050.9017
SYSTEM POWER CONSUMPTION	30W
EFFICACY	59.8lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	2700-6500K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	tunable white
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2963lm min. / 3380lm max
LUMEN OUTPUT	1794lm min. / 2046lm max
EFFICIENCY	60.5%
GLARE RATING	UGR < 19
WEIGHT	5,22 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	58,0 x 58,0 x 14,0 cm




Ceiling or wall lighting fixture for interiors, with direct light emission. $Turned\ aluminium\ structure\ in\ mat\ black\ and\ gold\ or\ white\ and\ gold\ polyacrylic\ paint.$ Pickled sheet metal wiring support plate in polyacrylic paint. $\ \, \text{Moulded polycarbonate micro-prismatic diffuser}.$








Technical drawing



Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270