# **PANZERI**

## Ginevra

220-240V AC dimmable (DALI/Push DIM)

P09280.080.0402





#### Data sheet

CODE	P09280.080.0402
SYSTEM POWER CONSUMPTION	71W
EFFICACY	94.97lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	8857lm
LUMEN OUTPUT	6743lm
EFFICIENCY	76.1%
GLARE RATING	UGR < 19
WEIGHT	10,07 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	18,0 x 90,0 x 90,0 cm




Ceiling or wall lighting fixture for interiors, with direct light emission.  $Turned\ aluminium\ structure\ in\ mat\ black\ and\ gold\ or\ white\ and\ gold\ polyacrylic\ paint.$ Pickled sheet metal wiring support plate in polyacrylic paint.  $\ \, \text{Moulded polycarbonate micro-prismatic diffuser}.$ 








### Technical drawing



### **Application**



#### Polar diagram



cd/klm C0 - C180 - - - C90 - C270