PANZERI

Ginevra

220-240V AC dimmable (DALI/Push DIM)

P09281.050.0402





Data sheet

CODE	P09281.050.0402
SYSTEM POWER CONSUMPTION	25W
EFFICACY	75.08lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3100lm
LUMEN OUTPUT	1877lm
EFFICIENCY	60.5%
GLARE RATING	UGR < 19
WEIGHT	5,22 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	58,0 x 58,0 x 14,0 cm




Ceiling or wall lighting fixture for interiors, with direct light emission. $Turned\ aluminium\ structure\ in\ mat\ black\ and\ gold\ or\ white\ and\ gold\ polyacrylic\ paint.$ Pickled sheet metal wiring support plate in polyacrylic paint. $\ \, \text{Moulded polycarbonate micro-prismatic diffuser}.$







Technical drawing








Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270