

PANZERI

Ginevra

220-240V AC dimmable (DALI/Push DIM)

P09281.050.0502

 white/gold



Data sheet


CODE	P09281.050.0502
SYSTEM POWER CONSUMPTION	25W
EFFICACY	75.08lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 80.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3100lm
LUMEN OUTPUT	1877lm
EFFICIENCY	60.5%
GLARE RATING	UGR < 19
WEIGHT	5,22 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	58,0 x 58,0 x 14,0 cm



Ceiling or wall lighting fixture for interiors, with direct light emission.
Turned aluminium structure in mat black and gold or white and gold polyacrylic paint.
Pickled sheet metal wiring support plate in polyacrylic paint.
Moulded polycarbonate micro-prismatic diffuser.



Technical drawing



Application



Polar diagram

