PANZERI

Superbold

220-240V AC dimmable (phase cut)
P09905.060.0504

brushed champagne

DIRECT LIGHT

Data sheet

CODE	P09905.060.0504
SYSTEM POWER CONSUMPTION	32W
EFFICACY	66.31lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (phase cut)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	4758lm
LUMEN OUTPUT	2122lm
EFFICIENCY	44.6%
WEIGHT	3,88 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	62,0 x 62,0 x 20,0 cm

Ceiling or wall lighting fixture for interiors, with direct light emission.
Turned steel structure in textured soft white, mat black, champagne, bronze, textured myrtle blue and textured natural terracotta polyacrylic paint.
Aluminium wiring support plate with polyacrylate paint finish.
Curved diffuser screen made of matt PMMA technopolymer.
DALI/Push DIM driver available on request.

Technical drawing



Application