PANZERI

Carl2

220-240V AC dimmable (1-10V/Push DIM) P12517.033.0403

Data sheet

CODE	P12517.033.0403
SYSTEM POWER CONSUMPTION	43W
EFFICACY	66.79lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	adjustable
BEAM ANGLE	30°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (1-10V/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	4102lm
LUMEN OUTPUT	2872lm
EFFICIENCY	70%
GLARE RATING	UGR < 16
WEIGHT	1,20 Kg
PROTECTION DEGREE	IP20
PACKING DIMENSIONS	16,0 x 39,0 x 16,0 cm




Ceiling or wall lighting fixture for interiors, with swivelling light beam. Pickled sheet metal ceiling/wall bracket in polyacrylic paint. Pickled sheet metal structure in white, black, bronze, mat brass or titanium polyacrylic paint. Die-cast aluminium joints with polyacrylic paint.

Die-cast aluminium projectors rotating on two axes in polyacrylic paint. Reflectors in thermoplastic material with chrome plated finish. Textured glass screens.

Anti-glare snoots in black thermoplastic material.

CE ERE 🗵

Technical drawing




Application

bronze



Polar diagram



cd/klm _____C0 - C180 = - - C90 - C270