

432 Ways

220-240V AC dimmable (DALI/Push DIM)

P12701.006.0502



Data sheet


CODE	P12701.006.0502
SYSTEM POWER CONSUMPTION	6,7W
EFFICACY	125,5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
BEAM ANGLE	29°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	858lm
LUMEN OUTPUT	753lm
EFFICIENCY	87.8%
WEIGHT	0.28 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	8,5 x 8,5 x 13,5 cm



Ceiling lighting fixture for interiors, with direct light emission.
 Extruded and milled aluminium structure, with polyacrylic paint finish in white, black, bronze, mat brass, textured olive green or textured natural terracotta.
 Lens holder not included, to be purchased separately.



Technical drawing



Polar diagram