

PANZERI

432 Ways

220-240V AC dimmable (DALI/Push DIM)

P12701.008.0402

white




Data sheet

CODE	P12701.008.0402
SYSTEM POWER CONSUMPTION	10,7W
EFFICACY	115,7lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1355lm
LUMEN OUTPUT	1157lm
EFFICIENCY	85,4%
WEIGHT	0,60 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	10,5 x 10,5 x 16,0 cm



Technical drawing



Polar diagram



Ceiling lighting fixture for interiors, with direct light emission.
Extruded and milled aluminium structure, with polyacrylic paint finish in white, black, bronze, mat brass, textured olive green or textured natural terracotta.
Lens holder not included, to be purchased separately.