

432 Ways

220-240V AC dimmable (DALI/Push DIM)

P12701.010.0502





Data sheet

CODE	P12701.010.0502
SYSTEM POWER CONSUMPTION	16,4W
EFFICACY	117,19lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2036lm
LUMEN OUTPUT	1875lm
EFFICIENCY	92,1%
WEIGHT	0,80 Kg
PROTECTION DEGREE	IP40
COLOUR TOLERANCES	SDCM 3
PACKING DIMENSIONS	12,5 x 12,5 x 19,0 cm



Technical drawing



Ceiling lighting fixture for interiors, with direct light emission.
Extruded and milled aluminium structure, with polyacrylic paint finish in white, black, bronze, mat brass, textured olive green or textured natural terracotta.
Lens holder not included, to be purchased separately.

Polar diagram