PANZERI

432 Ways

220-240V AC dimmable (phase cut)

P12701.010.0504





Data sheet

CODE	P12701.010.0504
SYSTEM POWER CONSUMPTION	16,4W
EFFICACY	117.19lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (phase cut)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2036lm
LUMEN OUTPUT	1875lm
EFFICIENCY	92.1%
WEIGHT	0,79 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	12,5 x 12,5 x 19,0 cm



Ceiling lighting fixture for interiors, with direct light emission. $\label{prop:continuous} \textbf{Extruded aluminium structure, with polyacrylic paint finish in white, black, bronze, mat}$ brass, textured olive green or textured natural terracotta.


Ceiling mounting bracket in bent sheet steel.







Technical drawing



Polar diagram