PANZERI

432 Ways

220-240V AC dimmable (phase cut)

P12701.010.0504





Data sheet

| CODE | P12701.010.0504 |
|--------------------------|-----------------------|
| SYSTEM POWER CONSUMPTION | 16,4W |
| EFFICACY | 117.19lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L90 (B10) 50.000h |
| COLOUR TEMPERATURE | 2700K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (phase cut) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 2036lm |
| LUMEN OUTPUT | 1875lm |
| EFFICIENCY | 92.1% |
| WEIGHT | 0,79 Kg |
| PROTECTION DEGREE | IP40 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 12,5 x 12,5 x 19,0 cm |
| - | |



Ceiling lighting fixture for interiors, with direct light emission. $\label{prop:continuous} \textbf{Extruded aluminium structure, with polyacrylic paint finish in white, black, bronze, mat}$ brass, textured olive green or textured natural terracotta.


Ceiling mounting bracket in bent sheet steel.







Technical drawing



Polar diagram