

# PANZERI

## 432 Ways

220-240V AC dimmable (DALI/Push DIM)

P12705.010.0402

 champagne




### Data sheet

|                          |                          |
|--------------------------|--------------------------|
| CODE                     | P12705.010.0402          |
| SYSTEM POWER CONSUMPTION | 16,4W                    |
| EFFICACY                 | 119,56lm/W               |
| LIGHT SOURCE             | LED                      |
| LIGHT SOURCE LIFETIME    | L90 (B10) 50.000h        |
| COLOUR TEMPERATURE       | 3000K Ra>90              |
| LIGHT DISTRIBUTION       | diffused                 |
| POWER SUPPLY             | 220-240V AC              |
| FREQUENCY                | 50/60Hz                  |
| ELECTRICAL CONFIGURATION | dimmable (DALI/Push DIM) |
| DRIVER                   | integrated included      |
| NOMINAL LUMINOUS FLUX    | 2077lm                   |
| LUMEN OUTPUT             | 1913lm                   |
| EFFICIENCY               | 92,1%                    |
| WEIGHT                   | 0,80 Kg                  |
| PROTECTION DEGREE        | IP40                     |
| COLOUR TOLLERANCES       | SDCM 3                   |
| PACKING DIMENSIONS       | 12,5 x 12,5 x 19,0 cm    |



Ceiling lighting fixture for interiors, with direct light emission.  
Extruded and milled aluminium structure, with polyacrylic paint finish in white, black, bronze, mat brass, textured olive green or textured natural terracotta.  
Lens holder not included, to be purchased separately.

### Technical drawing



### Polar diagram