


PANZERI

432 Ways

220-240V AC dimmable (phase cut)

P12705.010.0504

 champagne




Data sheet

CODE	P12705.010.0504
SYSTEM POWER CONSUMPTION	16,4W
EFFICACY	117,19lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (phase cut)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2036lm
LUMEN OUTPUT	1875lm
EFFICIENCY	92,1%
WEIGHT	0,79 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	12,5 x 12,5 x 19,0 cm



Ceiling lighting fixture for interiors, with direct light emission.
Extruded aluminium structure, with polyacrylic paint finish in white, black, bronze, mat brass, textured olive green or textured natural terracotta.
Ceiling mounting bracket in bent sheet steel.

Technical drawing



Polar diagram