PANZERI

432 Ways

220-240V AC dimmable (DALI/Push DIM)

P12727.008.0402





Data sheet

| CODE | P12727.008.0402 |
|--------------------------|--------------------------|
| SYSTEM POWER CONSUMPTION | 10,7W |
| EFFICACY | 116.9lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L90 (B10) 50.000h |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (DALI/Push DIM) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 1355lm |
| LUMEN OUTPUT | 1169lm |
| EFFICIENCY | 86.3% |
| WEIGHT | 0,00 Kg |
| PROTECTION DEGREE | IP40 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 0,0 x 0,0 x 0,0 cm |
| | |



Ceiling lighting fixture for interiors, with direct light emission. $\label{thm:extruded} \textbf{Extruded} \ \text{and} \ \textbf{milled} \ \textbf{aluminium} \ \textbf{structure,} \ \textbf{with} \ \textbf{polyacrylic} \ \textbf{paint} \ \textbf{finish} \ \textbf{in} \ \textbf{white,} \ \textbf{black,}$ bronze, mat brass, textured olive green or textured natural terracotta. Lens holder not included, to be purchased separately.







Technical drawing





