# **PANZERI**

## 432 Ways

220-240V AC dimmable (phase cut)

P12727.008.0504





#### Data sheet

CODE	P12727.008.0504
SYSTEM POWER CONSUMPTION	10,7W
EFFICACY	113.4lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (phase cut)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1328lm
LUMEN OUTPUT	1134lm
EFFICIENCY	85.4%
WEIGHT	0,60 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	10,5 x 10,5 x 16,0 cm




Ceiling lighting fixture for interiors, with direct light emission.  $\label{thm:extruded} \textbf{Extruded} \ \textbf{and} \ \textbf{milled} \ \textbf{aluminium} \ \textbf{structure,} \ \textbf{with} \ \textbf{polyacrylic} \ \textbf{paint} \ \textbf{finish} \ \textbf{in} \ \textbf{white,} \ \textbf{black,}$ bronze, mat brass, textured olive green or textured natural terracotta. Lens holder not included, to be purchased separately.







### Technical drawing







#### Polar diagram