


PANZERI

432 Ways

220-240V AC dimmable (phase cut)

P12729.008.0504

 textured natural terracotta



Data sheet


| | |
|--------------------------|-----------------------|
| CODE | P12729.008.0504 |
| SYSTEM POWER CONSUMPTION | 10,7W |
| EFFICACY | 113,4lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L90 (B10) 50.000h |
| COLOUR TEMPERATURE | 2700K Ra>90 |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 220-240V AC |
| FREQUENCY | 50/60Hz |
| ELECTRICAL CONFIGURATION | dimmable (phase cut) |
| DRIVER | integrated included |
| NOMINAL LUMINOUS FLUX | 1328lm |
| LUMEN OUTPUT | 1134lm |
| EFFICIENCY | 85,4% |
| WEIGHT | 0,60 Kg |
| PROTECTION DEGREE | IP40 |
| COLOUR TOLLERANCES | SDCM 3 |
| PACKING DIMENSIONS | 10,5 x 10,5 x 16,0 cm |



Ceiling lighting fixture for interiors, with direct light emission.
Extruded and milled aluminium structure, with polyacrylic paint finish in white, black, bronze, mat brass, textured olive green or textured natural terracotta.
Lens holder not included, to be purchased separately.



Technical drawing



Polar diagram