PANZERI

Zero Round

220-240V AC dimmable (DALI/Push DIM)

P15317.075.0502





Data sheet

CODE	P15317.075.0502
SYSTEM POWER CONSUMPTION	29W
EFFICACY	105.48lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3594lm
LUMEN OUTPUT	3059lm
EFFICIENCY	85.1%
WEIGHT	1,80 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	83,0 x 83,0 x 10,0 cm



Ceiling or wall lighting fixture for interiors, with direct and indirect light emission. Pickled sheet metal ceiling or wall bracket in polyacrylic paint.

Pickled sheet metal wall plate in polyacrylic paint.

Bended extruded aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.

Extruded polycarbonate diffuser with opaline finish.







Technical drawing

Application



Polar diagram

