PANZERI

Joe

220-240V AC ST.XA2115

Data sheet

CODE	ST.XA2115
SYSTEM POWER CONSUMPTION	max 50W
LIGHT SOURCE	LED retrofit / halogen
LIGHT SOURCE KIT	not included
COMPATIBLE SOURCES	max 50W GU10
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
WEIGHT	0,09 Kg
PROTECTION DEGREE	IP20
PACKING DIMENSIONS	10,0 x 8,0 x 10,0 cm









Lighting fixture for ceiling built-in installation for interiors, with direct light emission. Built-in structure for permanent false ceilings, in turned aluminium in white polyacrylic paint.

Light source retaining spring clip in stainless steel. Stainless steel spring clips for false ceiling fixing. Built-in hole dimension: Ø 75mm (Ø 3")

Application










F

GU10





PANZERI

Joe

Accessories / source

YLS001.050.1715

LED lamp 8,5W 250mA 35V 2700K Ra>90 806lm 35°.



YLS001.050.2515

LED lamp 8,5W 250mA 35V 3000K Ra>90 854lm 35°.



YLS001.050.2915

LED lamp 8,5W 250mA 35V 4000K Ra>90 1053lm 35°.



PANZERI

Joe

Accessories / power supply

XM6-15 UNI	LED driver, 2,5÷15W 60÷360mA.	19 mm "1,0
CE ERL 🗵 🗆 🎆]05m]	€0 50 ⊨ 115 mm 4 ½*
ХМ6-20 D/P MULTI С Є ЕПП 🗵 回 🎄	LED driver, 9,2÷28W 200÷900mA, 1-10V/DALI/Push DIM dimmable.	wiggin
xm6-25 d/p multi C € ERL 🗵 回 🚵	LED driver, 11÷25,6W 200÷900mA, DALI/Push DIM dimmable.	^E S S S S S S S S