PANZERI

Hilow Line

220-240V AC dimmer on cable

T10706.200.0522





Data sheet

CODE	T10706.200.0522
SYSTEM POWER CONSUMPTION	39W
EFFICACY	69.59lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B10) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmer on cable
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	4032lm
LUMEN OUTPUT	2714lm
EFFICIENCY	67.3%
WEIGHT	10,01 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



Floor lighting fixture for interiors, with indirect light emission.

Bearing base in "verde alpi" marble.

Extruded aluminium structure in mat black, bronze or mat brass polyacrylic paint.

Die-cast aluminium end caps in polyacrylic paint.

Extruded polycarbonate diffuser with opaline finish.

Supplied with 3m (118,1") long black fabric power cord complete with box with pushbutton for adjusting light intensity and plug adapter.







Technical drawing





Polar diagram

