# PANZERI

# Mark


24V DC X01701.055.0410

### Data sheet

| CODE                     | X01701.055.0410       |
|--------------------------|-----------------------|
| SYSTEM POWER CONSUMPTION | 17W                   |
| EFFICACY                 | 42.53lm/W             |
| LIGHT SOURCE             | LED                   |
| LIGHT SOURCE LIFETIME    | L80 (B20) 80.000h     |
| COLOUR TEMPERATURE       | 3000K Ra>90           |
| LIGHT DISTRIBUTION       | diffused              |
| POWER SUPPLY             | 24V DC                |
| DRIVER                   | remote not included   |
| NOMINAL LUMINOUS FLUX    | 2152lm                |
| LUMEN OUTPUT             | 723lm                 |
| EFFICIENCY               | 33.6%                 |
| WEIGHT                   | 1,05 Kg               |
| PROTECTION DEGREE        | IP20                  |
| COLOUR TOLLERANCES       | SDCM 3                |
| PACKING DIMENSIONS       | 12,5 x 63,0 x 14,0 cm |
|                          |                       |

CE ERE 🗵 🐵

## Technical drawing





white



Lighting fixture for ceiling or wall built-in installation for interiors, with direct light emission. Built-in structure in plasterboard, in aluminium in white polyacrylic paint. Reflector in aluminium in white polyacrylic paint.


Pickled sheet metal closing frame in white, black, bronze, mat brass or titanium polyacrylic paint.

Stainless steel spring clips for plasterboard fixing. Built-in hole dimension: 530x67mm (20,9x2,6")

## Application



#### Polar diagram



cd/klm \_\_\_\_\_C0 - C180 - - - C90 - C270