PANZERI

Aldecimo

220-240V AC bilevel dimming

X02201.030.0412

white



Data sheet

CODE	X02201.030.0412
SYSTEM POWER CONSUMPTION	21W
EFFICACY	41.57lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	bilevel dimming
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2732lm
LUMEN OUTPUT	873lm
EFFICIENCY	32%
WEIGHT	1,28 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	40,0 x 16,0 x 40,0 cm



Lighting fixture for wall built-in installation for interiors, with direct and indirect light

 $Total\ built-in\ structure\ in\ masonry\ or\ plasterboard,\ in\ pickled\ sheet\ metal\ in\ polyacrylic$ paint.

Aluminium dissipation plate.

 $\label{thm:modelled} \mbox{Modelled polycarbonate diffuser with opaline finish.}$

Pickled sheet metal closing plate in white polyacrylic paint.

Opening and closing click mechanism.

Pickled sheet metal brackets for plasterboard fixing.


Built-in hole dimension: 295x295mm (11,6x11,6")








Technical drawing








Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270