PANZERI

Ypsilon

220-240V AC ON-OFF

X07217.000.0401





Data sheet

CODE	X07217.000.0401
SYSTEM POWER CONSUMPTION	13W
EFFICACY	80.46lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1366lm
LUMEN OUTPUT	1046lm
EFFICIENCY	76.6%
WEIGHT	0,59 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	10,0 x 83,0 x 5,0 cm



Lighting fixture for wall semi-built-in installation for interiors, with indirect light

Pickled sheet metal bracket in white, black, bronze or mat brass polyacrylic paint, or in polished stainless steel.

Brass structure in white, black, bronze or mat brass polyacrylic paint, or with galvanic chrome plating.

Extruded polycarbonate diffuser with opaline finish.


Recessed housing for masonry in galvanized sheet metal.







Technical drawing



Application



Polar diagram

