PANZERI

Flat

220-240V AC ON-OFF

X07501.060.0401





Data sheet

CODE	X07501.060.0401
SYSTEM POWER CONSUMPTION	48W
EFFICACY	61.04lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B20) 60.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	5216lm
LUMEN OUTPUT	2930lm
EFFICIENCY	56.2%
WEIGHT	5,18 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	19,5 x 62,5 x 63,5 cm



Lighting fixture for ceiling built-in installation for interiors, with direct light emission. $\label{point:bearing} \textbf{Built-in bearing structure for modular false ceilings, in aluminium in polyacrylic paint.}$ Pickled sheet metal closing frames in white polyacrylic paint.

Modelled polycarbonate diffuser with opaline finish.

Equipped with inspection flap to access the terminal block.











Technical drawing



Polar diagram



cd/klm C0 - C180 - - - C90 - C270