# **PANZERI**

## Lola

500mA DC dimmable (DALI/Push DIM)

X12019.020.4002





#### Data sheet

CODE	X12019.020.4002
SYSTEM POWER CONSUMPTION	18W
EFFICACY	110.83lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>85
LIGHT DISTRIBUTION	adjustable
BEAM ANGLE	24°
POWER SUPPLY	500mA DC
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	remote included
NOMINAL LUMINOUS FLUX	2400lm
LUMEN OUTPUT	1995lm
EFFICIENCY	83.1%
GLARE RATING	UGR < 12
WEIGHT	0,52 Kg
PROTECTION DEGREE	IP20
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	12,0 x 29,5 x 11,0 cm



Lighting fixture for ceiling semi-built-in installation for interiors, with swivelling light

 $\label{polyacrylic} \textbf{Built-in ceiling plate for permanent false ceilings, in pickled sheet metal with polyacrylic}$ paint.

Turned brass joint.

 $\label{eq:decomposition} \mbox{Die-cast aluminium structure rotating on two axes in white, black, bronze, mat brass or $(1)$ and $(1)$ are sufficiently also always a sufficient problems of the sufficient problems. The sufficient problems is always always are sufficiently always are sufficien$ titanium polyacrylic paint.

Reflector in thermoplastic material with chrome plated finish.

Anti-glare snoot in black thermoplastic material.

Stainless steel spring clips for false ceiling fixing.


Equipped with 0,4m (15,7") long power cable. Built-in hole dimension: Ø 65mm (Ø 2,6")








# Technical drawing



### Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270