


# PANZERI

## Carl

350mA DC ON-OFF  
X12217.008.1701




### Data sheet

CODE	X12217.008.1701
SYSTEM POWER CONSUMPTION	12W
EFFICACY	87.5lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	flood
BEAM ANGLE	30°
POWER SUPPLY	350mA DC
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	remote included
NOMINAL LUMINOUS FLUX	1500lm
LUMEN OUTPUT	1050lm
EFFICIENCY	70%
GLARE RATING	UGR < 16
WEIGHT	0,27 Kg
PROTECTION DEGREE	IP20
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	13,0 x 15,0 x 9,0 cm



Lighting fixture for ceiling semi-built-in installation for interiors, with direct light emission.  
Built-in ceiling plate for permanent false ceilings, in die-cast aluminium with polyacrylic paint.  
Die-cast aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.  
Reflector in thermoplastic material with chrome plated finish.  
Textured glass screen.  
Anti-glare snoot in black thermoplastic material.  
Stainless steel spring clips for false ceiling fixing.  
Equipped with 0,4m (15,7") long power cable.  
Built-in hole dimension: Ø 42mm (Ø 1,7")

### Technical drawing



### Polar diagram

