PANZERI

Carl

350mA DC ON-OFF

X12217.008.2501





Data sheet

| CODE | X12217.008.2501 |
|----------------------------|----------------------|
| SYSTEM POWER CONSUMPTION | 12W |
| EFFICACY | 87.5lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L80 (B10) 50.000h |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | flood |
| BEAM ANGLE | 30° |
| POWER SUPPLY | 350mA DC |
| ELECTRICAL CONFIGURATION | ON-OFF |
| DRIVER | remote included |
| NOMINAL LUMINOUS FLUX | 1500lm |
| LUMEN OUTPUT | 1050lm |
| EFFICIENCY | 70% |
| GLARE RATING | UGR < 16 |
| WEIGHT | 0,27 Kg |
| PROTECTION DEGREE | IP20 |
| GLOW WIRE TEST PERFORMANCE | 850° |
| PACKING DIMENSIONS | 13,0 x 15,0 x 9,0 cm |





Lighting fixture for ceiling semi-built-in installation for interiors, with direct light

Built-in ceiling plate for permanent false ceilings, in die-cast aluminium with polyacrylic paint.

Die-cast aluminium structure in white, black, bronze, mat brass or titanium polyacrylic

 $\label{lem:reflector} \textit{Reflector} \ \textit{in} \ \textit{thermoplastic} \ \textit{material} \ \textit{with} \ \textit{chrome} \ \textit{plated} \ \textit{finish}.$


Textured glass screen.

Anti-glare snoot in black thermoplastic material.


Stainless steel spring clips for false ceiling fixing.

Equipped with 0,4m (15,7") long power cable.

Built-in hole dimension: Ø 42mm (Ø 1,7")



Polar diagram



<u>cd/klm</u> C0 - C180 - - - C90 - C270