PANZERI

Carl


700mA DC ON-OFF X12302.007.2501

Data sheet

CODE	X12302.007.2501
SYSTEM POWER CONSUMPTION	6,5W
EFFICACY	70.83lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	adjustable
BEAM ANGLE	34°
POWER SUPPLY	700mA DC
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	remote included
NOMINAL LUMINOUS FLUX	650lm
LUMEN OUTPUT	425lm
EFFICIENCY	65.4%
GLARE RATING	UGR < 12
WEIGHT	0,11 Kg
PROTECTION DEGREE	IP20
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	8,0 x 12,5 x 8,0 cm



Technical drawing



black





Lighting fixture for ceiling semi-built-in installation for interiors, with swivelling light beam.

Built-in ceiling plate for permanent false ceilings, in die-cast aluminium with polyacrylic paint.

Die-cast aluminium joint with polyacrylic paint. Die-cast aluminium structure rotating on two axes in white, black, bronze, mat brass or

titanium polyacrylic paint.


Reflector in thermoplastic material with chrome plated finish. Textured glass screen.

Anti-glare snoot in black thermoplastic material.

Stainless steel spring clips for false ceiling fixing.

Equipped with 0,4m(15,7") long power cable. Built-in hole dimension: Ø 42mm (Ø 1,7")

Polar diagram



Panzeri.it - 03/05/2024 - Carl - X12302.007.2501