PANZERI

Joe

220-240V AC ON-OFF

XA2115

white



Data sheet

CODE	XA2115
SYSTEM POWER CONSUMPTION	max 50W
EFFICACY	13.6lm/W
LIGHT SOURCE	LED retrofit / halogen
LIGHT SOURCE KIT	* included
COMPATIBLE SOURCES	LED retrofit bulb 7,5W GU10 3000K 60° Ra80 680lm (no dimming) * / max 50W GU10
COLOUR TEMPERATURE	3000K Ra>80
LIGHT DISTRIBUTION	wide flood
BEAM ANGLE	60°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
NOMINAL LUMINOUS FLUX	680lm
LUMEN OUTPUT	680lm
EFFICIENCY	100%
WEIGHT	0,09 Kg
PROTECTION DEGREE	IP20
PACKING DIMENSIONS	0,0 × 0,0 × 0,0 cm



Lighting fixture for ceiling built-in installation for interiors, with direct light emission. $\label{eq:built-instructure} \textbf{Built-in structure for permanent false ceilings, in turned aluminium in white or black}$ polyacrylic paint.

Light source retaining spring clip in stainless steel. Stainless steel spring clips for false ceiling fixing. Built-in hole dimension: Ø 75mm (Ø 3")














Technical drawing

Ø 6,7 Ø 2 ²/3"









Application



Polar diagram

