Brooklyn

24V DC

XG2033-200TRACK





Data sheet

CODE	XG2033-200TRACK
SYSTEM POWER CONSUMPTION	max 24W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
WEIGHT	1,48 Kg
PROTECTION DEGREE	IP40 IP20
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	6,0 x 6,0 x 214,0 cm
L (mm)	2010
L (in)	79 1/5"
ADVISED BRACKETS	3
HOLE (mm)	2015 x 40
HOLE (in)	79 2/5" x1 3/8"









Modular profile for ceiling or wall built-in installation for interiors, with direct light

Total built-in structure in plasterboard, in extruded aluminium in RAL 9003 white powder paint.

Extruded polycarbonate diffuser with opaline finish.


Equipped with disposal screen for smoothing, plastering and painting of the installation $% \left(1\right) =\left(1\right) \left(1\right)$

Light modules and driver to be ordered separately.

Fastening, joining and closing accessories to be ordered separately.

Built-in hole dimension: 2015x40mm (79,3x1,6")


Technical drawing



Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270

Brooklyn

Accessories / source XM006.012.0410 LED module, 125mm (5") 16 LED 2,2W 24V DC 3000K Ra>90 285lm. C€ EHI ŵ LED module, 500mm (19,7") 64 LED 8,6W 24V DC 3000K Ra>90 1140lm. XM006.050.0410 C€ [HI ⓓ ---- $Strip\ LED, 5000mm\ (196,9")\ 160\ LED/m\ 21,6W/m\ 24V\ DC\ 3000K\ Ra>80\ 3020lm/m,\ to\ be\ cut\ each\ 50mm$ YLR001.022.0110 C€ [H[ŵ alle a compa a alle a compa a compa a compa Strip LED, 5000mm (196,9") 168 LED/m 17,3W/m 24V DC 3000K Ra>90 1810lm/m, to be cut each 42mm (1,7"). YLR002.017.0410 C€ [H[® YLR002.017.0510 Strip LED, 5000mm (196,9") 168 LED/m 17,3W/m 24V DC 2700K Ra>90 1700lm/m, to be cut each 42mm C € ERI ŵ Strip LED, 5000mm (196,9") 168 LED/m 17,3W/m 24V DC 4000K Ra>90 1920lm/m, to be cut each 42mm YLR002.017.0610 C€ [H[ŵ YLR003.010.0410 Strip LED, 5000mm (196,9") 168 LED/m 9,6W/m 24V DC 3000K Ra>90 930lm/m, to be cut each 42mm (1,7"). C€ [H[® Strip LED, 5000mm (196,9") 168 LED/m 9,6W/m 24V DC 2700K Ra>90 882lm/m, to be cut each 42mm YLR003.010.0510 C€ [H[®

Strip LED, 5000mm (196,9") 168 LED/m 9,6W/m 24V DC 4000K Ra>90 980lm/m, to be cut each 42mm

(1,7")

YLR003.010.0610

C € EHI ŵ

Brooklyn

Accessories / power supply

XM100/24 DIM C € [FH] (m)	LED driver, 100W 24V DC, DALI/Push DIM dimmable.	
XM150/24 DIM	LED driver, 150W 24V DC, DALI/Push DIM dimmable.	
CE ERI ®		**************************************
XM18/24 DIM	LED driver, 18W 24V DC, DALI/Push DIM dimmable.	Mars 5.50 26.1
CE FAL (III)		## 175 mm 6 %*
XM35/24 DIM	LED driver, 35W 24V DC, DALI/Push DIM dimmable.	10 M
CE FAL (1)		
XM6-20 UNI	LED driver, 4*20W 250*700mA.	78° mm
CE ENI (m)		E 00 118 mm 4 2/n*
XM60/24 DIM	LED driver, 60W 24V DC, DALI/Push DIM dimmable.	Will see the second sec
CE FAL ®		1 2 255 mm 6 Hz
YDV.024.030.A01	LED driver, 30W 24V DC.	
CE ERL ®		
YDV.024.120.A01	LED driver, 120W 24V DC.	
CE FAL ®		
YDV.024.180.A01	LED driver, 180W 24V DC.	\$≥ \$.
CE EHI (III)		\$ [*]

Brooklyn

Accessories / connection

XM2033/34/32/31-S

Power cables.





Brooklyn

Accessories / diffusion

XM2033/34-WHI

White reflector with 1000mm (39,4") lenght to be cut.



CE EHI 🕸

XM2033/34/45/46-1200S

Extruded polycarbonate diffuser with opaline finish, 12000mm (472,4") long.



C € ERI ®

XM2033/34/45/46-600S

Extruded polycarbonate diffuser with opaline finish, 6000mm (236,2") long.



C€ [H[ŵ



XM2033/34/45/46-900S

Extruded polycarbonate diffuser with opaline finish, 9000mm (354,3") long.







Brooklyn

Accessories / fixing

XM2033-F

Drywall fixing bracket for trimless recessed profiles.



XM2033/34-L

CE EHI 🕸

Pair of fixing plates for recessed installation in brick wall or concrete.







XM2033/34/38/39P

Plate for hanging.





C€ [H[ŵ



Brooklyn

Accessories / junction

XM2033-U45	Two profiles level junction with 45° cut, for total built-in installation.	80mm 3177
C € EHI		·
XM2033-U90	Connection joint for two lines of modular profiles with level junction 90°, for total built-in installation.	_
CE FAI ŵ		900mm 8 17/5
		38mm 11/2*
XM2033-UT	Three profiles "T" level junction, for total built-in installation.	
CE FAI (III)		
XM2033-X	Four profiles "X" level junction, for total built-in installation.	
C € EHL ŵ		
XM2033/34-ANG	Two profiles perpendicular junction with 45° cut.	
CE EHL W		
XM2033/34-U	Linear junction.	
CE HI (III)		80mm 3 1/7"

Brooklyn

Accessories / closing

XM2033-T

C€ EHI ŵ

Pair of end caps with screws for trimless recessed profiles.



