# **PANZERI**

## Brooklyn

24V DC

XG2033-200TRACK PR





### Data sheet

CODE	XG2033-200TRACK PR
SYSTEM POWER CONSUMPTION	max 24W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	anti-glare
BEAM ANGLE	51° / 82°
POWER SUPPLY	24V DC
DRIVER	remote not included
GLARE RATING	UGR < 19
WEIGHT	1,48 Kg
PROTECTION DEGREE	IP40 IP20
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	6,0 x 6,0 x 214,0 cm
L (mm)	2010
L (in)	79 1/5"
ADVISED BRACKETS	3
HOLE (mm)	2015 x 40
HOLE (in)	79 2/5" ×1 3/8"



Modular profile for ceiling or wall built-in installation for interiors, with direct light

Total built-in structure in plasterboard, in extruded aluminium in RAL 9003 white powder paint.

Micro-prismatic extruded polycarbonate diffuser.

 $\label{prop:continuous} \mbox{Equipped with disposal screen for smoothing, plastering and painting of the installation}$ 

Light modules and driver to be ordered separately.


Fastening, joining and closing accessories to be ordered separately.

Built-in hole dimension: 2015x40mm (79,3x1,6")






### **Technical drawing**



### **Application**



### Polar diagram



cd/klm C0 - C180 - - - C90 - C270