Brooklyn


24V DC XG2033-300TRACK

Data sheet

CODE	XG2033-300TRACK
SYSTEM POWER CONSUMPTION	max 24W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
WEIGHT	2,21 Kg
PROTECTION DEGREE	IP40 IP20
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	6,0 x 6,0 x 314,0 cm
L (mm)	3010
L (in)	118 3/5"
ADVISED BRACKETS	4
HOLE (mm)	3015 x 40
HOLE (in)	118 4/5" x 1 3/8"



Technical drawing



white/opal screen



Modular profile for ceiling or wall built-in installation for interiors, with direct light emission.

Total built-in structure in plasterboard, in extruded aluminium in RAL 9003 white powder paint.

Extruded polycarbonate diffuser with opaline finish. Equipped with disposal screen for smoothing, plastering and painting of the installation surface.


Light modules and driver to be ordered separately. Fastening, joining and closing accessories to be ordered separately.

Built-in hole dimension: 3015x40mm (118,7x1,6")

Application



Polar diagram



cd/klm _____C0 - C180 - - - C90 - C270

Brooklyn

Accessories / source

XM006.012.0410	LED module, 125mm (5") 16 LED 2,2W 24V DC 3000K Ra>90 285lm.	
CE HII 🐵		<u>ka (1985)</u> - 2000 - A raa
XM006.050.0410	LED module, 500mm (19,7") 64 LED 8,6W 24V DC 3000K Ra>90 1140lm.	
CE HI		<u>. / * 100</u> - 200 - A ra
YLR005.010.0410	LED STRIP: 5m/5cm 9.6W/m 3000K CRI90 24V 1220lm/m	
CE ERE (m)		
YLR005.010.0510	LED STRIP: 5m /5cm 9.6W/m 2700K CRI90 24V 1100lm/m	
CE FHI		
YLR005.010.0610	LED STRIP: 5m /5cm 9.6W/m 4000K CRI90 24V 1300lm/m	
CE ERE 🐵		
YLR006.017.0410	LED STRIP: 5m /5cm 16.8W/m 3000K CRI90 24V 2070lm/m	
CE III		
YLR006.017.0510	LED STRIP: 5m /5cm 16.8W/m 2700K CRI90 24V 1900lm/m	
CE ERE 💿		
YLR006.017.0610	LED STRIP: 5m /5cm 16.8W/m 4000K CRI90 24V 2220lm/m	
CE ERI		

Brooklyn

Accessories / power supply

XM6-20 UNI	LED driver, 4÷20W 250÷700mA.	22 min 25
CE EAL		면 원 2
		118 mm 4 ²/ʒ*
YDV.024.030.A01	LED driver, 30W 24V DC.	and the second s
YDV.024.120.A01	LED driver, 120W 24V DC.	40 mm 40 mm 40 mm 10 mm 10 mm
YDV.024.180.A01	LED driver, 180W 24V DC.	2)≥ 2)• ———————————————————————————————————

Brooklyn

Accessories / connection

XM2033/34/32/31-S

Power cables.

CE ERE 🐵

 \sim

Brooklyn

Accessories / diffusion

XM2033/34-WHI	White reflector with 1000mm (39,4") lenght to be cut.	
XM2033/34/45/46-1200S CEERE	Extruded polycarbonate diffuser with opaline finish, 12000mm (472,4*) long.	The second s
XM2033/34/45/46-600S	Extruded polycarbonate diffuser with opaline finish, 6000mm (236,2") long.	Table
XM2033/34/45/46-900S	Extruded polycarbonate diffuser with opaline finish, 9000mm (354,3") long.	etili

Brooklyn

Accessories / fixing

XM2033-F Ce IHI 🐵	Drywall fixing bracket for trimless recessed profiles.	
XM2033/34-L Ce III 🐵	Pair of fixing plates for recessed installation in brick wall or concrete.	
XM2033/34/38/39P	Plate for hanging.	

Brooklyn

Accessories / junction

XM2033-U45	Two profiles level junction with 45° cut, for total built-in installation.	
хм2033-U90 СС ІП	Connection joint for two lines of modular profiles with level junction 90°, for total built-in installation.	30mm 195 199 1199 1199 1199 1199 1199 1199
хм2033-UT СС ІШ 💿	Three profiles "T" level junction, for total built-in installation.	
хм2033-х СС ІП (Ф)	Four profiles "X" level junction, for total built-in installation.	
XM2033/34-ANG	Two profiles perpendicular junction with 45° cut.	<u>120m</u> 41/- 30m 17/-
XM2033/34-U	Linear junction.	80mm 31/r

Brooklyn

Accessories / closing

XM2033-T

Pair of end caps with screws for trimless recessed profiles.



