

PANZERI

Brooklyn

24V DC
XG2033-50TRACK PR

 white/prismatic screen



Data sheet

CODE	XG2033-50TRACK PR
SYSTEM POWER CONSUMPTION	max 24W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	anti-glare
BEAM ANGLE	51° / 82°
POWER SUPPLY	24V DC
DRIVER	remote not included
GLARE RATING	UGR < 19
WEIGHT	0,38 Kg
PROTECTION DEGREE	IP40 IP20
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	6,0 x 6,0 x 65,0 cm
L (mm)	510
L (in)	20"
ADVISED BRACKETS	2
HOLE (mm)	515 x 40
HOLE (in)	20 2/7" x 1 3/8"



Modular profile for ceiling or wall built-in installation for interiors, with direct light emission.
Total built-in structure in plasterboard, in extruded aluminium in RAL 9003 white powder paint.
Micro-prismatic extruded polycarbonate diffuser.
Equipped with disposal screen for smoothing, plastering and painting of the installation surface.
Light modules and driver to be ordered separately.
Fastening, joining and closing accessories to be ordered separately.
Built-in hole dimension: 515x40mm (20,3x1,6")

Technical drawing

Application



Polar diagram

