PANZERI

Brooklyn Trim

24V DC

XG2034-50TRACK





Data sheet

CODE	XG2034-50TRACK
SYSTEM POWER CONSUMPTION	max 24W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
WEIGHT	0,32 Kg
PROTECTION DEGREE	IP40 IP20
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	6,0 x 6,0 x 65,0 cm
L (mm)	510
L (in)	20"
ADVISED BRACKETS	2
HOLE (mm)	515 x 40
HOLE (in)	20 2/7" x 1 3/8"





Modular profile for ceiling or wall built-in installation for interiors, with direct light emission

Built-in structure in plasterboard, in extruded aluminium in RAL 9003 white powder paint.


 ${\sf Extruded\ polycarbonate\ diffuser\ with\ opaline\ finish}.$

Light modules and driver to be ordered separately.

Fastening, joining and closing accessories to be ordered separately.

Built-in hole dimension: 515x40mm (20,3x1,6")


Technical drawing



Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270