PANZERI

# Corner

24V DC
XG2045-100TRACK

white

DIRECT LIGHT


## Data sheet

| | |
|---|---|
| CODE | XG2045-100TRACK |
| SYSTEM POWER CONSUMPTION | max 24W/m |
| LIGHT SOURCE | LED |
| LIGHT DISTRIBUTION | diffused |
| POWER SUPPLY | 24V DC |
| DRIVER | remote not included |
| GLARE RATING | UGR < 19 |
| WEIGHT | 0,78 Kg |
| PROTECTION DEGREE | IP40 IP20 |
| PACKING DIMENSIONS | 8,0 x 8,0 x 114,0 cm |
| L (mm) | 1010 |
| L (in) | 39 4/5" |



Modular profile for ceiling or wall perimeter installation for interiors, with direct light emission.
Hidden structure for plasterboard panels, in extruded aluminium in RAL 9003 white powder paint.
Extruded polycarbonate diffuser with opaline finish.
Light modules and driver to be ordered separately.
Fastening, joining and closing accessories to be ordered separately.


## Technical drawing




## Application



## Polar diagram



PANZERI

# Corner

## Accessories / source

XM006.012.0410

LED module, 125mm (5") 16 LED 2,2W 24V DC 3000K Ra>90 285lm.



XM006.050.0410

LED module, 500mm (19,7") 64 LED 8,6W 24V DC 3000K Ra>90 1140lm.



YLR005.010.0410

LED STRIP: 5m/5cm 9.6W/m 3000K CRI90 24V 1220lm/m

YLR005.010.0510

LED STRIP: 5m /5cm 9.6W/m 2700K CRI90 24V 1100lm/m

YLR005.010.0610

LED STRIP: 5m /5cm 9.6W/m 4000K CRI90 24V 1300lm/m

YLR006.017.0410

LED STRIP: 5m /5cm 16.8W/m 3000K CRI90 24V 2070lm/m

YLR006.017.0510

LED STRIP: 5m /5cm 16.8W/m 2700K CRI90 24V 1900lm/m

YLR006.017.0610

LED STRIP: 5m /5cm 16.8W/m 4000K CRI90 24V 2220lm/m

YLR007.022.0410

LED STRIP: 5m /4.2cm 22W/m 3000K CRI90 24V 2700lm/m

PANZERI

# Corner

**Accessories / source**

YLR007.022.0510 LED STRIP: 5m /4.2cm 22W/m 2700K CRI90 24V 2490lm/m

YLR007.022.0610 LED STRIP: 5m /4.2cm 22W/m 4000K CRI90 24V 2750lm/m


PANZERI

# Corner

## Accessories / power supply


YDV.024.030.A01

LED driver, 30W 24V DC.



YDV.024.120.A01

LED driver, 120W 24V DC.



YDV.024.180.A01

LED driver, 180W 24V DC.




PANZERI

# Corner

## Accessories / diffusion


XM2033/34/45/46-1200S

Extruded polycarbonate diffuser with opaline finish, 12000mm (472,4") long.




XM2033/34/45/46-600S

Extruded polycarbonate diffuser with opaline finish, 6000mm (236,2") long.



XM2033/34/45/46-900S

Extruded polycarbonate diffuser with opaline finish, 9000mm (354,3") long.



PANZERI

# Corner

## Accessories / junction


XM2045-ANG 3

Connection joint for two lines of modular profiles with internal perpendicular junction 90°, for perimetral installation.




XM2045-ANG 4

Connection joint for two lines of modular profiles with external perpendicular junction 90°, for perimetral installation.




XM2045-U

Linear junction.





XM2045-U90 1

Connection joint for two lines of modular profiles with internal level junction 90°, for perimetral installation.



XM2045-U90 2

Connection joint for two lines of modular profiles with external level junction 90°, for perimetral installation.



PANZERI

# Corner

## Accessories / closing

XM2045-T

Pair of end caps with screws.

