Corner

24V DC

XG2045-200TRACK





Data sheet

XG2045-200TRACK
max 24W/m
LED
diffused
24V DC
remote not included
UGR < 19
1,45 Kg
IP40 IP20
8,0 x 8,0 x 214,0 cm
2010
79 1/5"









Modular profile for ceiling or wall perimeter installation for interiors, with direct light

 $\label{eq:hidden} \mbox{Hidden structure for plasterboard panels, in extruded aluminium in RAL~9003~white}$ powder paint.

Extruded polycarbonate diffuser with opaline finish.

Light modules and driver to be ordered separately.

Fastening, joining and closing accessories to be ordered separately.


Technical drawing



Application



Polar diagram



Corner

Accessories / source			
XM006.012.0410 C € FHI (iii)	LED module, 125mm (5") 16 LED 2,2W 24V DC 3000K Ra>90 285lm.		
XM006.050.0410 C € [EHI (m)	LED module, 500mm (19,7") 64 LED 8,6W 24V DC 3000K Ra>90 1140lm.		
YLR005.010.0410 C € [FHI] (1)	LED STRIP: 5m/5cm 9.6W/m 3000K CRI90 24V 1220lm/m		
YLR005.010.0510 C € [HI] (m)	LED STRIP: 5m /5cm 9.6W/m 2700K CRI90 24V 1100lm/m		
YLR005.010.0610 C € [HI] (m)	LED STRIP: 5m /5cm 9.6W/m 4000K CRI90 24V 1300lm/m		
YLR006.017.0410 ☐ [FHI] (III)	LED STRIP: 5m /5cm 16.8W/m 3000K CRI90 24V 2070lm/m		
YLR006.017.0510 C € [FIII] (m)	LED STRIP: 5m /5cm 16.8W/m 2700K CRI90 24V 1900lm/m		
YLR006.017.0610 C € [FIII] (m)	LED STRIP: 5m /5cm 16.8W/m 4000K CRI90 24V 2220lm/m		
YLR007.022.0410	LED STRIP: 5m /4.2cm 22W/m 3000K CRI90 24V 2700lm/m		

CE ERI ®

Corner

Accessories / source

YLR007.022.0510

LED STRIP: 5m /4.2cm 22W/m 2700K CRI90 24V 2490lm/m





YLR007.022.0610

LED STRIP: 5m /4.2cm 22W/m 4000K CRI90 24V 2750lm/m





Corner

Accessories / power supply



Corner

Accessories / diffusion

CE EHI 🕸

XM2033/34/45/46-1200S

Extruded polycarbonate diffuser with opaline finish, 12000mm (472,4") long.



XM2033/34/45/46-600S

Extruded polycarbonate diffuser with opaline finish, 6000mm (236,2") long.









XM2033/34/45/46-900S

Extruded polycarbonate diffuser with opaline finish, 9000mm (354,3") long.





Corner

Accessories / junction

XM2045-ANG 3

C€ [HI ⓓ

Connection joint for two lines of modular profiles with internal perpendicular junction 90° , for perimetral installation.



XM2045-ANG 4

C€ EHI ŵ

Connection joint for two lines of modular profiles with external perpendicular junction 90°, for perimetral installation.



XM2045-U

Linear junction.





XM2045-U901

C € EHI ®

Connection joint for two lines of modular profiles with internal level junction $90\,^\circ$, for perimetral installation.



XM2045-U902

Connection joint for two lines of modular profiles with external level junction 90° , for perimetral installation.





Corner

Accessories / closing

XM2045-T

Pair of end caps with screws.





