### Corner

24V DC

XG2045-300TRACK





#### Data sheet

XG2045-300TRACK
max 24W/m
LED
diffused
24V DC
remote not included
UGR < 19
2,05 Kg
IP40 IP20
8,0 x 8,0 x 314,0 cm
3010
118 3/5"









Modular profile for ceiling or wall perimeter installation for interiors, with direct light

 $\label{eq:hidden} \mbox{Hidden structure for plasterboard panels, in extruded aluminium in RAL~9003~white}$ powder paint.

Extruded polycarbonate diffuser with opaline finish.

Light modules and driver to be ordered separately.

Fastening, joining and closing accessories to be ordered separately.


### **Technical drawing**



### **Application**



### Polar diagram



## Corner

Accessories / source  XM006.012.0410  CE EHL	LED module, 125mm (5") 16 LED 2,2W 24V DC 3000K Ra>90 285lm.	
XM006.050.0410 C € [HI] (m)	LED module, 500mm (19,7") 64 LED 8,6W 24V DC 3000K Ra>90 1140lm.	
YLR005.010.0510 <b>C € EHL</b>	LED STRIP: 5m /5cm 9.6W/m 2700K CRI90 24V 1100lm/m	
YLR005.010.0610	LED STRIP: 5m /5cm 9.6W/m 4000K CRI90 24V 1300lm/m	
YLR006.017.0410 <b>C € EHI </b>	LED STRIP: 5m /5cm 16.8W/m 3000K CRI90 24V 2070lm/m	
YLR006.017.0510	LED STRIP: 5m /5cm 16.8W/m 2700K CRI90 24V 1900lm/m	
YLR006.017.0610  C € [H] (ii)	LED STRIP: 5m /5cm 16.8W/m 4000K CRI90 24V 2220lm/m	
YLR007.022.0410 <b>C € EHL </b>	LED STRIP: 5m /4.2cm 22W/m 3000K CRI90 24V 2700lm/m	
YLR007.022.0510	LED STRIP: 5m /4.2cm 22W/m 2700K CRI90 24V 2490lm/m	

CE ERI ®

## Corner

### Accessories / source

YLR007.022.0610

LED STRIP: 5m /4.2cm 22W/m 4000K CRI90 24V 2750lm/m



### Corner

### Accessories / power supply



### Corner

#### Accessories / diffusion

XM2033/34/45/46-1200S

Extruded polycarbonate diffuser with opaline finish, 12000mm (472,4") long.



XM2033/34/45/46-600S

Extruded polycarbonate diffuser with opaline finish, 6000mm (236,2") long.



CE EHI 🕸

...., , ...



XM2033/34/45/46-900S

Extruded polycarbonate diffuser with opaline finish, 9000mm (354,3") long.



### Corner

#### Accessories / junction

XM2045-ANG 3

C€ [HI ⓓ

Connection joint for two lines of modular profiles with internal perpendicular junction  $90^\circ$ , for perimetral installation.



XM2045-ANG 4

C€ EHI ŵ

Connection joint for two lines of modular profiles with external perpendicular junction 90°, for perimetral installation.



XM2045-U

Linear junction.





XM2045-U901

C € EHI ®

Connection joint for two lines of modular profiles with internal level junction  $90\,^\circ$  , for perimetral installation.



XM2045-U902

Connection joint for two lines of modular profiles with external level junction  $90^{\circ}$ , for perimetral installation.







## Corner

### Accessories / closing

XM2045-T

Pair of end caps with screws.





