PANZERI

Nolita

220-240V AC dimmable (DALI/Push DIM)

XG23801.090.0402





Data sheet

CODE	XG23801.090.0402
SYSTEM POWER CONSUMPTION	35W
EFFICACY	55.57lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3912lm
LUMEN OUTPUT	1945lm
EFFICIENCY	49.7%
WEIGHT	2,43 Kg
PROTECTION DEGREE	IP40 IP20
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	12,5 x 98,0 x 12,5 cm
L (mm)	891
L (in)	35 1/9"
ADVISED BRACKETS	2
HOLE (mm)	896 x 75
HOLE (in)	35 2/3" x 3"



Modular profile for ceiling or wall built-in installation for interiors, with direct light

Total built-in structure in plasterboard, in extruded aluminium in RAL 9003 white powder paint.

Reflector retaining spring clips in stainless steel.

Aluminium reflector in RAL 9003 white polyacrylic paint.

Equipped with light modules and dimmable driver.

Equipped with disposal screen for smoothing, plastering and painting of the installation surface.

 $\label{polycarbonate} \textbf{Extruded polycarbonate diffuser with opaline finish or micro-prismatic to be ordered}$

Fastening, joining and closing accessories to be ordered separately.

Built-in hole dimension: 896x75mm (35,3x3")








Technical drawing







Application



Polar diagram

