# **PANZERI**

# Nolita Trim

220-240V AC ON-OFF

XG23901.060.0401





#### Data sheet

| Data sneet                 |                       |
|----------------------------|-----------------------|
| CODE                       | XG23901.060.0401      |
| SYSTEM POWER CONSUMPTION   | 24,5W                 |
| EFFICACY                   | 54lm/W                |
| LIGHT SOURCE               | LED                   |
| COLOUR TEMPERATURE         | 3000K Ra>90           |
| LIGHT DISTRIBUTION         | diffused              |
| POWER SUPPLY               | 220-240V AC           |
| FREQUENCY                  | 50/60Hz               |
| ELECTRICAL CONFIGURATION   | ON-OFF                |
| DRIVER                     | integrated included   |
| NOMINAL LUMINOUS FLUX      | 2608lm                |
| LUMEN OUTPUT               | 1296lm                |
| EFFICIENCY                 | 49.7%                 |
| WEIGHT                     | 1,82 Kg               |
| PROTECTION DEGREE          | IP40 IP20             |
| SHOCK RESISTANCE RATING    | IK08                  |
| GLOW WIRE TEST PERFORMANCE | 850°                  |
| PACKING DIMENSIONS         | 14,5 x 64,5 x 14,5 cm |
| L (mm)                     | 591                   |
| L (in)                     | 23 2/7"               |
| ADVISED BRACKETS           | 2                     |
| HOLE (mm)                  | 596 x 75              |
| HOLE (in)                  | 23 1/2" x 3"          |
|                            |                       |



Modular profile for ceiling or wall built-in installation for interiors, with direct light

Built-in structure in plasterboard, in extruded aluminium in RAL 9003 white powder paint.

Reflector retaining spring clips in stainless steel.

Aluminium reflector in RAL 9003 white polyacrylic paint.

Equipped with light modules and driver.

Extruded polycarbonate diffuser with opaline finish or micro-prismatic to be ordered

Fastening, joining and closing accessories to be ordered separately.


Built-in hole dimension: 596x75mm (23,5x3")








## **Technical drawing**







## **Application**



#### Polar diagram

