Bronx

24V DC

XG24701.100.0099





Data sheet

CODE	XG24701.100.0099
SYSTEM POWER CONSUMPTION	17,2W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
WEIGHT	0,97 Kg
PROTECTION DEGREE	IP40 IP20
PACKING DIMENSIONS	8,0 x 114,0 x 8,0 cm
L (mm)	1010
L (in)	39 4/5"
ADVISED BRACKETS	2
HOLE (mm)	1015 x 50
HOLE (in)	40" x 2"









Modular profile for ceiling or wall built-in installation for interiors, with direct light

Total built-in structure in plasterboard, in extruded aluminium in RAL 9003 white or black powder paint.


Recessed extruded polycarbonate diffuser with opaline finish.


Light modules and driver to be ordered separately.

Fastening, joining and closing accessories to be ordered separately.

Built-in hole dimension: 1015x50mm (40x2")

Technical drawing






Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270

Bronx

Accessories / source

XM005.012.0410

LED module, 125mm (5") 16 LED 2,2W 24V DC 3000K Ra>90 285lm.









XM005.050.0410

LED module, 500mm (19,7") 64 LED 8,6W 24V DC 3000K Ra>90 1140lm.









Bronx

Accessories / power supply

XM100/24 DIM CE EHL I	LED driver, 100W 24V DC, DALI/Push DIM dimmable.	\$\frac{1}{2}\$
XM150/24 DIM C € ERI ŵ	LED driver, 150W 24V DC, DALI/Push DIM dimmable.	
XM18/24 DIM	LED driver, 18W 24V DC, DALI/Push DIM dimmable.	# 175 mm 6 169
XM35/24 DIM C € [HI] (iii)	LED driver, 35W 24V DC, DALI/Push DIM dimmable.	
XM6-20 UNI	LED driver, 4÷20W 250÷700mA.	25 25 25 25 25 25 25 25 25 25 25 25 25 2
XM60/24 DIM	LED driver, 60W 24V DC, DALI/Push DIM dimmable.	# ≥ ≥ ≥ ≥ ≥ ≥ ≥ ≥ ≥
YDV.024.030.A01	LED driver, 30W 24V DC.	E E E E E E E E E E
YDV.024.120.A01 C € [HI]	LED driver, 120W 24V DC.	
YDV.024.180.A01 C € [H] [LED driver, 180W 24V DC.	1) 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

Bronx

Accessories / connection

XM2033/34/32/31-S

Power cables.





Bronx

Accessories / fixing

XM24700.201.0099

Drywall fixing bracket kit.





Bronx

Accessories / junction

XM24700.301.0099

Linear junction kit.







XM24701.302.0099

CE EHI 🕸

Connection joint for two lines of modular profiles with level junction 90° , for total built-in installation.





Bronx

Accessories / closing

XM24701.202.0099

Pair of end caps with screws.





