### **Bronx**

24V DC

XG24702.100.0099





#### Data sheet

CODE	XG24702.100.0099
SYSTEM POWER CONSUMPTION	17,2W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
WEIGHT	0,97 Kg
PROTECTION DEGREE	IP40 IP20
PACKING DIMENSIONS	8,0 x 114,0 x 8,0 cm
L (mm)	1010
L (in)	39 4/5"
ADVISED BRACKETS	2
HOLE (mm)	1015 x 50
HOLE (in)	40" x 2"
·	









Modular profile for ceiling or wall built-in installation for interiors, with direct light

Total built-in structure in plasterboard, in extruded aluminium in RAL 9003 white or black powder paint.


Recessed extruded polycarbonate diffuser with opaline finish.


Light modules and driver to be ordered separately.

Fastening, joining and closing accessories to be ordered separately.

Built-in hole dimension: 1015x50mm (40x2")

### Technical drawing






#### **Application**



#### Polar diagram



cd/klm C0 - C180 - - - C90 - C270

## Bronx

#### Accessories / source

XM005.012.0410

LED module, 125mm (5") 16 LED 2,2W 24V DC 3000K Ra>90 285lm.









XM005.050.0410

LED module, 500mm (19,7") 64 LED 8,6W 24V DC 3000K Ra>90 1140lm.









# Bronx

### Accessories / power supply

XM100/24 DIM	LED driver, 100W 24V DC, DALI/Push DIM dimmable.	
XM150/24 DIM	LED driver, 150W 24V DC, DALI/Push DIM dimmable.	
XM18/24 DIM	LED driver, 18W 24V DC, DALI/Push DIM dimmable.	
XM35/24 DIM C € EHI ŵ	LED driver, 35W 24V DC, DALI/Push DIM dimmable.	
XM6-20 UNI	LED driver, 4÷20W 250÷700mA.	E 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
XM60/24 DIM	LED driver, 60W 24V DC, DALI/Push DIM dimmable.	#
YDV.024.030.A01	LED driver, 30W 24V DC.	#
YDV.024.120.A01	LED driver, 120W 24V DC.	
YDV.024.180.A01	LED driver, 180W 24V DC.	#

# Bronx

### Accessories / connection

XM2033/34/32/31-S

Power cables.





# Bronx

### Accessories / fixing

XM24700.201.0099

Drywall fixing bracket kit.





## Bronx

### Accessories / junction

XM24700.301.0099

Linear junction kit.







XM24702.302.0099

C€ EHE ŵ

Connection joint for two lines of modular profiles with level junction  $90^\circ$ , for total built-in installation.





# Bronx

## Accessories / closing

XM24702.202.0099

Pair of end caps with screws.





