Harlem

24V DC

XG25101.100.0099





Data sheet

CODE	XG25101.100.0099
SYSTEM POWER CONSUMPTION	17W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
WEIGHT	0,45 Kg
PROTECTION DEGREE	IP40 IP20
PACKING DIMENSIONS	6,0 x 6,0 x 114,0 cm
L (mm)	1010
L (in)	39 4/5"
HOLE (mm)	1015 x 55
HOLE (in)	40" x 2 1/6"









Modular profile for ceiling or wall built-in installation for interiors, with direct light

Total built-in structure in plasterboard, in extruded aluminium in RAL 9003 white powder paint.

Extruded polycarbonate diffuser with opaline finish.

Equipped with disposal screen for smoothing, plastering and painting of the installation $% \left(1\right) =\left(1\right) \left(1\right)$

Light modules and driver to be ordered separately.

Joining and closing accessories to be ordered separately.

Built-in hole dimension: 1015x55mm (40x2,2")

Technical drawing








Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270

Harlem

Accessories / source

YLR002.017.0410

Strip LED, 5000mm (196,9") 168 LED/m 17,3W/m 24V DC 3000K Ra>90 1810lm/m, to be cut each 42mm (1,7").



YLR002.017.0510

Strip LED, 5000mm (196,9") 168 LED/m 17,3W/m 24V DC 2700K Ra>90 1700lm/m, to be cut each 42mm



YLR002.017.0610

Strip LED, 5000mm (196,9") 168 LED/m 17,3W/m 24V DC 4000K Ra>90 1920lm/m, to be cut each 42mm (1,7").

CE EHI



YLR003.010.0410

Strip LED, 5000mm (196,9") 168 LED/m 9,6W/m 24V DC 3000K Ra>90 930lm/m, to be cut each 42mm (1,7").

CE EHI 🕸



Strip LED, 5000mm (196,9") 168 LED/m 9,6W/m 24V DC 2700K Ra>90 882lm/m, to be cut each 42mm





YLR003.010.0610

Strip LED, 5000mm (196,9") 168 LED/m 9,6W/m 24V DC 4000K Ra>90 980lm/m, to be cut each 42mm (1,7").







Harlem

Accessories / power supply

XM100/24 DIM	LED driver, 100W 24V DC, DALI/Push DIM dimmable.	
XM150/24 DIM	LED driver, 150W 24V DC, DALI/Push DIM dimmable.	
XM18/24 DIM	LED driver, 18W 24V DC, DALI/Push DIM dimmable.	
XM35/24 DIM C € EHI ŵ	LED driver, 35W 24V DC, DALI/Push DIM dimmable.	
XM6-20 UNI	LED driver, 4÷20W 250÷700mA.	E 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
XM60/24 DIM	LED driver, 60W 24V DC, DALI/Push DIM dimmable.	#
YDV.024.030.A01	LED driver, 30W 24V DC.	#
YDV.024.120.A01	LED driver, 120W 24V DC.	
YDV.024.180.A01	LED driver, 180W 24V DC.	#

Harlem

Accessories / junction

XM27000.301.0099

Linear junction kit.







Harlem

Accessories / closing

YTC25101.K02

Pair of end caps with screws.





