East

220-240V AC

XGQ1004-GL





Data sheet

CODE	XGQ1004-GL	
SYSTEM POWER CONSUMPTION	max 50W	
LIGHT SOURCE	LED retrofit / halogen	
LIGHT SOURCE KIT	not included	
COMPATIBLE SOURCES	max 50W GU10	
LIGHT DISTRIBUTION	diffused	
POWER SUPPLY	220-240V AC	
FREQUENCY	50/60Hz	
WEIGHT	0,56 Kg	
PROTECTION DEGREE	IP20	
PACKING DIMENSIONS	17,0 x 20,0 x 12,0 cm	

















12,5 x 12,5 5" x 5"

Lighting fixture for ceiling built-in installation for interiors, with direct light emission. Total built-in plaster structure for masonry or plasterboard.

Light source retaining spring clip in stainless steel.

Flat frosted glass diffuser.


Fixing brackets in micro-perforatd sheet metal.

Recessed housing for masonry in galvanized sheet metal to be ordered separately. Built-in hole dimension: 125x125mm (4,9x4,9")

Technical drawing













East

Accessories / source

YLL001.050.2201

PAR16 LED lamp GU10 7,5W 220-240V AC 3000K Ra>80 608lm 60° , not dimmable, white colour.

CE EHI 🗵 🗆 🚳 🧥 005ml

YLL002.050.2201

PAR16 LED lamp GU10 7,5W 220-240V AC 3000K Ra>80 608lm 60°, not dimmable, black colour.

YLS001.050.1715

LED lamp 8,5W 250mA 35V 2700K Ra>90 806lm 35°.

YLS001.050.2515

LED lamp 8,5W 250mA 35V 3000K Ra>90 854lm 35°.

YLS001.050.2915

LED lamp 8,5W 250mA 35V 4000K Ra>90 1053lm 35°.

East

Accessories / power supply



East

Accessories / fixing

XM1004/1004-GL/1030

Galvanized sheet housing to be recessed in brick wall or concrete.

