

PANZERI

East

220-240V AC


XGR0997

● plaster



Data sheet

CODE	XGR0997
SYSTEM POWER CONSUMPTION	max 50W
LIGHT SOURCE	LED retrofit / halogen
LIGHT SOURCE KIT	not included
COMPATIBLE SOURCES	max 50W GU10
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
WEIGHT	0,26 Kg
PROTECTION DEGREE	IP20
PACKING DIMENSIONS	16,0 x 11,0 x 8,0 cm



Lighting fixture for ceiling or wall built-in installation for interiors, with direct light emission.

Total built-in plaster structure for plasterboard.

Light source retaining spring clip in stainless steel.

Micro-perforated sheet metal brackets for plasterboard fixing.

Built-in hole dimension: \varnothing 100mm (\varnothing 3,9")

Technical drawing

\varnothing 6,3

\varnothing 2 1/2"



\varnothing 9,8

\varnothing 3 9/16"

12
4 3/4"

GU5,3

12,5
5"

YLS001:050..._15

13,5
5 1/8"

GU10

14,5
5 9/16"

YLL001:050..._01
YLL002:050..._01



\varnothing 10
 \varnothing 4"

Application




PANZERI

East

Accessories / source

YLL001.050.2201 PAR16 LED lamp GU10 7,5W 220-240V AC 3000K Ra>80 608lm 60°, not dimmable, white colour.



YLL002.050.2201 PAR16 LED lamp GU10 7,5W 220-240V AC 3000K Ra>80 608lm 60°, not dimmable, black colour.



YLS001.050.1715 LED lamp 8,5W 250mA 35V 2700K Ra>90 806lm 35°.



YLS001.050.2515 LED lamp 8,5W 250mA 35V 3000K Ra>90 854lm 35°.



YLS001.050.2915 LED lamp 8,5W 250mA 35V 4000K Ra>90 1053lm 35°.




PANZERI

East

Accessories / power supply


XM6-15 UNI

LED driver, 2,5÷15W 60÷360mA.



XM6-20 D/P MULTI

LED driver, 9,2÷28W 200÷900mA, 1-10V/DALI/Push DIM dimmable.



XM6-25 D/P MULTI

LED driver, 11÷25,6W 200÷900mA, DALI/Push DIM dimmable.

